



Exposed Internal Lining (Black)

Application: Pre-finished internal lining

Thickness: 10mm

Size: 1200mm x 2400mm, 2700mm, 3000mm special order

Install Method: Brad nail or screw for bracing GS1 spacing

Certifications and Ecolabels: EPD, GECA, Declare

10mm Exposed Internal Lining

saveBOARD - Upcycled Building Materials

-7.4

Carbon Footprint
kgCO₂e/m²





Exposed Internal Lining (White Noise)

Application: Pre-finished internal lining

Thickness: 10mm

Size: 1200mm x 2400mm, 2700mm, 3000mm special order

Install Method: Brad nail or screw for bracing GS1 spacing

Certifications and Ecolabels: EPD, GECA, Declare

10mm Exposed Internal Lining

saveBOARD - Upcycled Building Materials

-7.4

Carbon Footprint
kgCO₂e/m²



Exposed Internal Lining (Blue)

Application: Pre-finished internal lining

Thickness: 10mm

Size: 1200mm x 2400mm, 2700mm, 3000mm special order

Install Method: Brad nail or screw for bracing GS1 spacing

Certifications and Ecolabels: EPD, GECA, Declare

10mm Exposed Internal Lining

saveBOARD - Upcycled Building Materials

-7.4

Carbon Footprint
kgCO₂e/m²



Exposed Internal Lining (Community)

Application: Pre-finished internal lining

Thickness: 10mm

Size: 1200mm x 2400mm, 2700mm, 3000mm special order

Install Method: Brad nail or screw for bracing GS1 spacing

Certifications and Ecolabels: EPD, GECA, Declare

10mm Exposed Internal Lining

saveBOARD - Upcycled Building Materials

-7.4

Carbon Footprint
kgCO₂e/m²

